













PM-010/PM-132 PCMCIA 2xRS232 1MBaud

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 2 port RS232
- PCMCIA socket size
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



PM-010: PCMCIA 2xRS232 1MBaud

PM-132 PCMCIA 2xRS232 **RUGGED 1MBaud**



Description

A PCMCIA type II card providing two independent RS232 serial ports. Velocity megabaud data transfer rates and the 128 byte deep FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your laptop. The detachable cables allow the PC card to stay in the laptop without risk of damage during transit. Drivers for Windows 32 bit and 64 bit Operating Systems including Windows 95/98/2000, XP, Server 2003, Vista, Server 2008 and Windows 7.

Being mobile no longer limits your options. Standard and ruggedised card options to suit your needs.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support! Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 7 32 bit 64 bit Editions
- Windows Vista 32 bit 64 bit editions
- Windows XP 32 bit 64 bit editions
- Windows 2000

As well as: full product documentation, a thorough troubleshooting quide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.







ORDER Description PCMCIA 2xRS232 1MBaud PCMCIA 2xRS232 RUGGED 1MBaud

Code PM-010 PM-132



PCMCIA 2xRS232 1MBaud

PM-010/PM-132: Full Specification

PM-010/PM-132: Full Sp	ecilication	
Port	Ports	2 x RS232
Pin 1 DCD RS232 Pinout (9 Pin Male)	Connector	DB9 Connector - 9 Pin Male
Pin 2 RXD Pin 1 Pin 5 Pin 3 TXD Image: Control of the pin 1 Image: Control of the pin 1	FIFO size	128 RX FIFO + 128 TX FIFO
Pin 4 DTR Pin 5 GND	Operating Distance	EIA - RS232 Standard
Pin 6 DSR Pin 7 RTS Pin 8 CTS Pin 6 Pin 9	Cable	2 Port Cable: DB9 connector 9 Pin Male
Pin 8 CTS Pin 9 RI		
Port Settings	Baud Rate	921,600
921,600 > > > > > > > baud	Data Bits	5,6,7 or 8
	Parity	Odd, Even, None, Mark or Space
	Stop Bits	1, 1.5 or 2
	Flow Control	
	Tx/Rx Modes	Point to Point
	,	
Interface	OS Compatibility	Microsoft Windows 7 32 bit 64 bit Editions
	, ,	Windows Vista 32 bit 64 bit Editions
PCMCIA		Windows XP 32 bit 64 bit Editions
		Microsoft Windows 2000
	BUS	PCMCIA
Approvals	Other Approvals	AEO C-TPAT Microsoft Certified Gold Partner WEEE RoHS
Approvals	• • • • • • • • • • • • • • • • • • • •	
	Microsoft Approvals	Microsoft Certified Gold Partner Windows 7 32 bit 64 bit Editions Windows Vista 32 bit 64 bit edi-
		tions
		Windows XP 32 bit 64 bit editions Windows 2000
General	PCB Layers	4
	Power Consumption	210mA @ 5V, 20mA @ 12V
	Weight	0.029 kg
	Size	PCMCIA Type II: 85l x 54w x 5h mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	PCMCIA 2xRS232 1MBaud
		2 Port Cable: DB9 connector 9 Pin Male
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
	зарроге	staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
***	Made In	Manufactured in the UK by Brainboxes Winner 2005 European
Elektra O5 European Electronics Industry Awards		Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume
Made in the UK		users. More Info: sales@brainboxes.com